



1. **Cylinder**
2. **Claw**
3. **Inlet Filter**
4. **Protection Sheet**

PRODUCT DESCRIPTION

Dry and non-contact Zinisan dry tip hook vacuum pumps uses the air much more efficiently. As a sealing element in vacuum formation no oil is needed. The vacuum pump is completely oil-free. Working efficiency oil tip is much higher than vacuum pumps. At the same time more energy consumption is low. The vacuum pump is for a friction area unlike oily types for periodic maintenance can work for a long time without the need.

Teknik Özellikler Technical Data		ZKV140	ZKV200	ZKV250	ZKV325	ZKV500
Nominal Kapasite Nominal Displacement	50 Hz - m ³ / h	140 m ³ / h	200 m ³ / h	250 m ³ / h	325 m ³ / h	500 m ³ / h
Vakum Verimi Ultimate Pressure	mmHg	680	680	680	680	680
Motor Gücü Nominal Motor Rating	50 Hz - kW	3	4	5,5	7,5	11
Motor Devri Nominal Motor Speed	50 Hz - d/d	2800	2800	2800	2800	2800
Ses Seviyesi Noise Level	50 Hz - db(A)	80	80	82	82	83
Çalışma Sıcaklığı Operation Temperature	50 Hz - °C	80	80	80	80	80
Yaklaşık Ağırlık Approximate Weight	kg.	150	170	185	215	260